

Semaphore indicator Ø30.5mm Round

Brand :- MIMIC Model : MIMIC-SP-30.5



Salient Features

1. Voltage: 24V,110V, 220,250 VDC

2. Mounting: Panel mounting

3. Body: PBT Fire retardent

4. 100 % Made in India product.

5. Model name :- MIMIC-SP-30.5

6. Indoor duty :- IP 52

7. LED Based having long life, 50000 hours

8. Cutout size:- Ø30.5mm

Technical Specification

- ◆ Insulation voltage:- AC, DC 1000V
- ◆ Operational Voltage:-24V,110V, 220,250 VDC
- Voltage Fluctuation Range :- ± 15%
- ◆ Rated Operational Current :- 11mA max
- Insulation Resistance :- $1000m\Omega$ over
- ◆ Impulse Withstand Voltage :- +4500V, 3Times For Each Pole(1.2/50µs)
- ◆ Shock Resistance :- 490m/s²
- ◆ Durability :- Over 10000 cycles
- ◆ Degree Of Protection :- IP52
- ◆ Operating Temperature :- -20 to 60° c
- ◆ Storage Temperature :- -30 to 75° c
- ♦ Relative Humidity :- 45 to 85 %
- ◆ Altitude :- Max 2000m
- ◆ Compatible Copper Conductor :- AWG 20 to14
- ◆ Mounting Plate Thickness :- 1 to 6 mm
- ◆ Confirming to Standard :- IEC 60947-5-1

IEC 60947-1

Certificate of conformity is awarded to

Steam Airetric controls

In recognition of the organization's compliance to relevan clauses of Low Voltage Directive 2014/35/EU and in conformity with the harmonized standards

ty with the narmonized standards

EN 60947-5-1:2017

for the product

Indicator Light

(Semaphore Round 22mm Diameter, Semaphore Square

22mm Diameter, Semaphore Indicator 30.5mm Diameter,

Semaphore Indicator 32mm Diameter, Semaphore Indicator 42mm

Diameter, Semaphore Indicator 72mm Diameter)

CE/IN/006

Report No./TCF Reference

Date of issue 31 st May, 2018

Applications:-

- Used in situations that require visual simulation of the circuit or operating state of a device & indication of the fault position in addition to the 'ON' & 'OFF' positions.
- Suitable for monitoring power breakers & disconnectors in complex transformers substations which are represented in form of mimic diagrams of relatively small dimensions.
- Suitable for automatic status indication of isolators, earth switches, circuit breakers & PT ON/OFF etc. on 'MIMIC' diagrams.








Circuit Breaker close

Circuit Breaker open


Panel cutout Dimensions







Connection diagram



- +1 : Red Vertical
- +2 : Green Horizontal
- C : Common

Ordering Code :-

Sr. No.	Code :-	Details :-
S21	MIMIC-SP-30-24-DC-RO	MIMIC LED Semaphore Indicator 30.5 Cutout Voltage 24 VDC - Round
S22	MIMIC-SP-30-110-DC-RO	MIMIC LED Semaphore Indicator 30.5 Cutout Voltage 110 VDC - Round
S23	MIMIC-SP-30-125-DC-RO	MIMIC LED Semaphore Indicator 30.5 Cutout Voltage 125 VDC - Round
S24	MIMIC-SP-30-220-DC-RO	MIMIC LED Semaphore Indicator 30.5 Cutout Voltage 220 VDC - Round
S25	MIMIC-SP-30-250-DC-RO	MIMIC LED Semaphore Indicator 30.5 Cutout Voltage 250 VDC - Round

Steam Airetric Controls

Plot No A/34, Additional Ambernath MIDC, Anand Nagar, Ambernath(East), Dist. Thane, Maharashtra, India, 421506 Email:mimic.sales@gmail.com, sales@mimicproducts.in,

Website:www.mimicproducts.com www.mimicproducts.in 9821252022 9321153191